

TS250F_230V

panel saw

- stable and precise table saw with aluminium sliding table
- largely dimensioned, stable outrigger table
- smoothly running saw blade height and angle adjustment
- large and precision-ground grey cast iron table with extension
- cross cut fence tilts 45° (left/right) and extensible (1230 - 2275 mm)
- rip fence with quick release clamp
- saw blade tilt (90-45°)

included in delivery: T.C.T. (Tungsten-Carbide-Tipped) general purpose blade with $\text{Ø} 254 \times 30 \times 3,0$ mm- 36 teeth, sliding table, edging shoe, push stick, sliding wood, table extension / widening, extensible cross-cut fence



**YOUR
JOB.
OUR
TOOLS.**

TS250F_230V

panel saw



technical details

motor power s6 in W	2900	motor power s1 in W	2100
voltage	230V / 50Hz	table size in mm	800 x 350
table height in mm	900	dust collector port in mm	Ø 100 (Ø30)
sliding table in mm	1650 x 250	outrigger table in mm	595 x 460
table extension in mm	405 x 210	table widening in mm	800 x 320
total dimensions in mm	2180(-3225) x 2930 x 1150	max. cutting height 90° in mm	80
max. trimming in mm	1250	max. cutting height 45° in mm	50
max. cutting width at parallel fence in mm	640	sawblade in mm	254 (/30)
sawblade speed in min-1	4000	sound power level in dB(A)	95,7
sound pressure level in dB(A)	86,5	net weight in kg	190
gross weight in kg	233	packaging height in mm	1.035
packaging width in mm	760	packaging length in mm	970
EAN code	9120039903927		

**YOUR
JOB.
OUR
TOOLS.**